



	<b>T60KT</b>
<b>Capacity (Distributed)</b>	<b>60,000 lbs.</b>
<b>Trailer Weight</b>	<b>12,560 lbs.</b>
<b>Stationary Deck Length</b>	<b>6' 0"</b>
<b>Tilt Deck Length</b>	<b>25' 6"</b>
<b>Tongue Length</b>	<b>7' 0"</b>
<b>Overall Length</b>	<b>38' 10"</b>
<b>Overall Width</b>	<b>102"</b>
<b>Deck Height</b>	<b>35"</b>
<b>Hitch</b>	<b>Drawbar eye</b>
<b>Landing Gear</b>	<b>Dual 2-speed landing gear</b>
<b>Safety Chains</b>	<b>1/2" x 36" Grade 70 (Adjustable)</b>
<b>Deck Latch</b>	<b>Air Actuated</b>
<b>Underride Protection</b>	<b>Air Actuated</b>
<b>Cushion Cylinder</b>	<b>5" x 12" (Air Actuated Optional)</b>
<b>Load Securement</b>	<b>22 ea. Chain Slots (D-Rings Optional)</b>
<b>Storage Compartment</b>	<b>Lockable Tool/Chain &amp; Binder Storage</b>
<b>Axles</b>	<b>3 ea. 23,000 lb.</b>
<b>Hubs</b>	<b>8 on 275mm – Oil Bath</b>
<b>Brakes</b>	<b>12-1/4" x 7-1/2" Air – 2S/2M ABS</b>
<b>Suspension</b>	<b>Hutch 9700 Tri-axle – 25K HD Springs</b>
<b>Tires</b>	<b>235/75R 17.5 – Load range H</b>
<b>Decking</b>	<b>2" Apitong in High Traffic area's</b>